

Your reliable  
partner in  
Temperature  
Control Units




## TEMP 120 M

Pressurized-water temperature control unit up to 120 °C

- ❖ Energy efficient pump
- ❖ Easy operation
- ❖ Temperature deviation alarm function
- ❖ Low noise



Equipment:	Standard	Optional
Automatic restart	•	
Temperature deviation alarm	•	
Automatic water refilling	•	
Leakage control during operation	•	
Pressure relief after stop		•
Mould draining		•
Automatic cool down function	•	
Flow measuring Vortex		•
Connection for external PT 100 sensor		•
Service indicator (hour counter)	•	
Serial interface 20 mA CL		•
Analog interface 4-20 mA		•
Profibus		•
Ethernet/IP		•
Profinet		•
Devicenet		•



## Technical Specifications:

COOLING WATER TEMPERATURE [ $\Delta T$ ]		
Max outlet temperature	120 °C	
Heating capacity	27 kW (opt. 36 kW)	
Heat transfer fluid	Water	
Tank volumen	12 Liter	
Pump	std.	
Type	M4	M5
Flow rate max. l/min	85	115
Pressure max. Bar	5,6	5,8
Power kW	1	1,5
Cooling capacity at $\Delta T = 60$ °C	std.	
Type	I2	I4
kW	15	28
Connections in/out	1/2"	
Operating voltage std.	3x400V/50Hz	
Dimensions (L x W x H)	900 x 270 x 640 mm	